

INKJET PRINTER SMTJET SJ22S 3304

STARFIRE PRINTER



StarFire
SG - 1024

Fully Upgraded New Model, More magnificent Outlook.
7000W Larger power heating & infrared drying system.
Improved feeding system, platform, air suction etc.
4 head Speed 250m²/h




- Double mute linear rail, all aluminum alloy beam, assures resolution.
- All steel nozzle printhead, inner heating&circulation, design life time 8 years.
- High precision platform, pinch roller, added feeding motor to adjust direction&speed.
- 7000W Infrared heating fan, matched with high density ink, fast drying & ink saving.
- All spare parts adopts famous brand, high performance, long lifetime, super stable.
- Nozzle heating & ink circulating,double negative pressure, keep printing smoothly.



IGUS Tank Chain



25L Double Negative Pressure



Double Feeding System



Imported Large Capacity Filters



Imported Servo Motor




Segmented Air Suction Control




Taiwan Hiwin Double Mute Guider Rail



Infrared air-drying System



All Aluminium Alloy Beam



High Performance Control System

SMTJET Starfire Solvent Printer

Printer Model	SJ22S 3304(2H)	SJ22S 3304(4H)
Printing Width	3.2M	
Ink Drop	10PL/25PL	
Printing Speed	2PASS 125m ² /h	2PASS 250m ² /h
	3PASS 90m ² /h	3PASS 180m ² /h
	4PASS 70m ² /h	4PASS 140m ² /h
Resolution	600*1080DPI	
Color	16.7 million CMYK	
Image format	TIFF, JPG, EPS , PDF	

Note: The parameter varies due to different PC configuration and settings. Detail information is subject to real product.

RIP software	Maintop (Optional Photoprint, Onyx)
Operation system	PC System : win7 64bit / win10 64bit CPU : Intel i5以上 Ram:4G Hard Disk:120G SSD + 500G HDD Port:USB2.0
Power supply	AC220V ,50HZ ± 10% ,UPS is required
Temperature/ Humidity	Temperature 0°C-40°C , Humidity 60%-70%
Power consumption	3000W
Take up system	Optional Take up/ Independent Take up system
G.W/N.W	1300 Kgs /1150 Kgs
Packing Dimension	501*111*170cm