

# INKJET PRINTER SMTJET SJ22S 3308 PRINTER



4/8 Konica 512i/1024i Printhead, speed up to 480m<sup>2</sup>/h  
Split body design, can load 4 sets in 20ft container




- Hiwin mute linear rail. all aluminum alloy beam, assures resolution.
- High precision platform, pinch roller, fine feeding&take up, neat and efficiency.
- Infrared drying system, matched with high density ink, fast drying and ink saving.
- Stable negative pressure, keep printing without ink break.
- All spare parts adopts famous brand, high performance, long lifetime, super stable.



IGUS Tank Chain




Negative Pressure



Feeding System



HCFA Servo Motor



Taiwan Hiwin Mute Guider Rail



Infrared air-drying System



Electric glass cartridge



High Performance Control System

## SMTJET Solvent Printer-Split Body

| Printer Model  | KM512i-30PL               |                      | KM1024i-30PL         |                            | KM1024i-13PL               |                      | RIP software          | Maintop (Optional Photoprint, Onyx)   |
|----------------|---------------------------|----------------------|----------------------|----------------------------|----------------------------|----------------------|-----------------------|---|
| Head Qty       | 4 pcs                     | 8 pcs                | 4 pcs                | 8 pcs                      | 4 pcs                      | 8 pcs                | Operation system      | PC System : win7 64bit / win10 64bit<br>CPU : Intel i5 / Ram:4G / 120G SSD + 500G HDD / Port:USB2.0 |
| Printing Speed | 2 PASS                    | 130m <sup>2</sup> /h | 253m <sup>2</sup> /h | 1PASS 253m <sup>2</sup> /h | 1PASS 480m <sup>2</sup> /h | 110m <sup>2</sup> /h | Power supply          | AC220V, 50HZ ± 10% , UPS is required  |
|                | 3 PASS                    | 90m <sup>2</sup> /h  | 165m <sup>2</sup> /h | 2PASS 129m <sup>2</sup> /h | 2PASS 253m <sup>2</sup> /h | 75m <sup>2</sup> /h  | Temperature/ Humidity | Temperature 0°C-40°C , Humidity 60%-70%   |
|                | 4 PASS                    | 55m <sup>2</sup> /h  | 131m <sup>2</sup> /h | 3PASS 90m <sup>2</sup> /h  | 3PASS 180m <sup>2</sup> /h | 60m <sup>2</sup> /h  | Power consumption     | 3000W   |
| Printing Width | 3.2M                      |                      |                      |                            |                            |                      | Take up system        | Optional Take up/ Independent Take up system  |
| Resolution     | 600*1080DPI               |                      |                      |                            |                            |                      | G.W/N.W               | 1193 Kgs / 1050 Kgs   |
| Color          | CMYK                      |                      |                      |                            |                            |                      | Packing Dimension     | 496*110*110 cm  |
| Image format   | BMP, TIFF, EPS, PDF, JPEG |                      |                      |                            |                            |                      |                       |   |

Note: The parameter varies due to different PC configuration and settings. Detail information is subject to real product.