INKJET PRINTER SMTJET 3308 1024i




4/8 Konica 512i/1024i Printhead, speed up to 480m²/h Split body design, can load 4 sets in 20ft container



- Hiwin mute linear rail. all aluminum alloy beam, assures resolution.
- High precision platform, pinch roller, fine feeding&take up, neat and efficiency.
- Infrared drying system, matched with high density ink, fast drying and ink saving.
- Stable negative pressure, keep printing without ink break.
- All spare parts adopts famous brand, high performance, long lifetime, super stable.



IGUS Tank Chain



Taiwan Hiwin Mute Guider Rail



Negative Pressure



Infrared air-drying System



Feeding System



Electric glass cartridge



HCFA Servo Motor



High Performance Control System

Printer Parameters

Printer Model		KM512i-30PL		KM1024i-30PL		KM1024i-13PL	
Head Qty		4 pcs	8 pcs	4 pcs	8 pcs	4 pcs	8 pcs
Printing Speed	2 PASS	130m²/h	260m²/h	1PASS 240m²/h	1 PASS 480m²/h	110m²/h	220m²/h
	3 PASS	90m²/h	180m²/h	2 PASS 130m²/h	2 PASS 260m²/h	75m²/h	150m²/h
	4 PASS	55m²/h	110m²/h	3 PASS 90m²/h	3 PASS 180m²/h	60m²/h	120m²/h
Printing Width		3.2M					
Resolution		600*1080DPI					
Color		СМҮК					
Image format		BMP, TIFF, EPS, PDF, JPEG					

 $Note: The \ parameter \ varies \ due \ to \ different \ PC \ configuration \ and \ settings. \ Detail \ information \ is \ subject \ to \ real \ product.$

RIP software	Maintop (Optional Photoprint, Onyx)				
Operation system	PC System: win7 64bit / win10 64bit CPU: Intel i5 / Ram:4G / 120G SSD + 500G HDD / Port:USB2.0				
Power supply	AC220V,50HZ±10%,UPS is required				
Temperature/ Humidity	Temperature 0°C-40°C,Humidity 60%-70%				
Power consumption	3000W				
Take up system	Optional Take up/Independent Take up system				
G.W/N.W	NW: 1200 Kgs GW:1380 Kgs				
Packing Dimension	496*110*110 cm				